

# **ENSIGN DRAIN**

# Long/Medium Radius Bend 88° ED02L/ED02M

## **DESCRIPTION**

The long/medium radius bend is designed to offer a smooth transition of direction within a pipe system.

#### **RECOMMENDED USE**

- Domestic use
- Wastewater
- Rainwater
- Runoff water
- Hot effluents

# **STANDARDS & APPROVALS**

- Industry product standard: BS EN 877
- Range fire classification: A2, s1, d0

# **IDENTIFICATION LABEL**





#### **MATERIALS & COATINGS**

- Cast iron
- Internally and externally coated grey, powder epoxy resin coating, min. average thickness 150µm

#### TECHNICAL FEATURES

- Hot water resistance: 24hr @ 95°C
- Thermal cycle resistance: 1500 cycles between 15°C and 93°C
- Chemical resistance for 1 ≤ pH ≤ 13, up to 80°C
- Salt spray resistance internal coating: more than 3000h
- Salt spray resistance external coating: more than 1500h

### **ENVIRONMENTAL DATA**

- Percentage of recycled content: 99%
- Recycling information: Cast iron is 100% recyclable through the existing recycling industrial network.


Data source: Environmental Product Declaration S-P-02191



# **ENSIGN DRAIN**

Long/Medium Radius Bend 88° ED02L/ED02M





DN	L	н	W	A	В	WEIGHT (KG)	PRODUCT CODE
100	326	333	110	269	180	4.8	191774
150*	357	363	160	274	150	8.7	191775
200*	477	456	210	339	175	13.9	291510

### Accessories:

- $\rightarrow$ 0.4l grey touch up paint 216318
- →Recommended couplings for connections ED001/ED004/EC002HP
- →For connection from Timesaver Drain to Ensign, please use the TD02 stepped coupling

This document is provided for information purposes, and our company reserves the right to modify the information contained herein at any time. Our company declines all responsibility of materials that do not comply with the rules prescribed in this document as well with the standards, the technical documents and the applicable professional standards. Any orders placed will be subject to our General Terms and Conditions of Sale, available on request. The drawings and/or images are the exclusive property of Pam Building and are confidential. They must not be reproduced or disclosed to any third party without written consent. They may only be used for the purpose for which they were issued and are returnable on request.

<sup>\* 150</sup>mm and 200mm are medium radius