

# **ENSIGN DRAIN**

# Long Tail Bend 45° ED055

# **DESCRIPTION**

The long tail bend is designed to replicate the short radius bend, but with one of the spigot ends offering a longer tail. This feature allows for a jointless connection should the bend need to penetrate through wall or slab.

#### **RECOMMENDED USE**

- Domestic use
- Wastewater
- Rainwater
- Runoff water
- Hot effluents

### **STANDARDS & APPROVALS**

- Industry product standard: BS EN 877
- Range fire classification: A2, s1, d0

# **IDENTIFICATION LABEL**





#### **MATERIALS & COATINGS**

- Cast iron
- Internally and externally coated grey, powder epoxy resin coating, min. average thickness 150µm

#### TECHNICAL FEATURES

- Hot water resistance: 24hr @ 95°C
- Thermal cycle resistance: 1500 cycles between 15°C and 93°C
- Chemical resistance for 1 ≤ pH ≤ 13, up to 80°C
- Salt spray resistance internal coating: more than 3000h
- Salt spray resistance external coating: more than 1500h

## **ENVIRONMENTAL DATA**

- Percentage of recycled content: 99%
- Recycling information: Cast iron is 100% recyclable through the existing recycling industrial network.

Data source: Environmental Product Declaration S-P-02191

DN	L	н	w	A	В	С	D	WEIGHT (KG)	PRODUCT CODE
100	337	141	110	70	250	180	260	4.0	191778

#### Accessories:

 $\rightarrow$ 0.4l grey touch up paint - 216318

- →Recommended couplings for connections ED001/ED004/EC002HP
- →For connection from Timesaver Drain to Ensign, please use the TD02 stepped coupling

Product Data Sheet - Pam Building - June 2025