

ENSIGN SOIL Short Radius Bend 15° EF002

DESCRIPTION

The short radius bend is designed to offer a smooth transition of direction within a pipe system.

The short radius bend conforms to BS 12056-2 and can be used for Soil, Vent and rainwater systems.

RECOMMENDED USE

- Domestic use
- Wastewater
- Rainwater
- Runoff water
- Hot effluents

STANDARDS & APPROVALS

- Industry product standard: BS EN 877
- Range fire classification: A1

IDENTIFICATION LABEL





MATERIALS & COATINGS

- Cast Iron
- Internally and externally coated red-brown, anti-corrosive epoxy powder coating, average thickness 150 µm internally and 70µm externally

TECHNICAL FEATURES

- Hot water resistance: 24hr @ 95°C
- Thermal cycle resistance: 1500 cycles between 15°C and 93°C
- Chemical resistance for 2>ph>12
- Salt spray resistance internal coating: more than 350hrs.


ENVIRONMENTAL DATA

- Percentage of recycled content: 99%
- Recycling information: Cast Iron is 100% recyclable through the existing recycling industrial network.


Data source: Environmental Product Declaration S-P-02190

pam building ENSIGN SOIL

Short Radius Bend 15° EF002







DN	L	н	w	Α	В	WEIGHT (KG)	PRODUCT CODE
50	66	80	58	40	66	0.4	191433
70	90	98	78	45	76	0.7	191438
100	121	112	110	50	83	1.3	191443
150	148	134	135	65	108	2.5	191455
200	227	184	210	80	129	4.6	155932
400	452	292	429	121	180	19.3	269726

This document is provided for information purposes, and our company reserves the right to modify the information contained herein at any time. Our company declines all responsibility of materials that do not comply with the rules prescribed in this document as well with the standards, the technical documents and the applicable professional standards. Any orders placed will be subject to our General Terms and Conditions of Sale, available on request. The drawings and/or images are the exclusive property of Pam Building and are confidential. They must not be reproduced or disclosed to any third party without written consent. They may only be used for the purpose for which they were issued and are returnable on request.