

ENSIGN SOIL Short Radius Bend 88° EF002

DESCRIPTION

The short radius bend is designed to offer a smooth transition of direction within a pipe system.

The short radius bend conforms to BS 12056-2 and can be used for soil, vent and rainwater systems.

RECOMMENDED USE

- Domestic use
- Wastewater
- Rainwater
- Runoff water
- Hot effluents

STANDARDS & APPROVALS

- Industry product standard: BS EN 877
- Range fire classification: A1

IDENTIFICATION LABEL





MATERIALS & COATINGS

- Cast Iron
- Internally and externally coated red-brown, anti-corrosive epoxy powder coating, average thickness 150 µm internally and 70µm externally

TECHNICAL FEATURES

- Hot water resistance: 24hr @ 95°C
- Thermal cycle resistance: 1500 cycles between 15°C and 93°C
- Chemical resistance for 2>ph>12
- Salt spray resistance internal coating: more than 350hrs.

ENVIRONMENTAL DATA


- Percentage of recycled content: 99%
- Recycling information: Cast Iron is 100% recyclable through the existing recycling industrial network.


Data source: Environmental Product Declaration S-P-02190

pam building ENSIGN SOIL

Short Radius Bend 88° EF002







DN	L	н	w	А	В	WEIGHT (KG)	PRODUCT CODE
50	104	107	58	75	49	0.8	191437
70	130	132	78	90	54	1.4	191442
200	288	291	210	180	81	8.1	191462
250	360	363	274	220	89	13.5	191463
300	427	431	326	260	105	27.4	191431
400	644	651	429	466	223	59.0	265224

This document is provided for information purposes, and our company reserves the right to modify the information contained herein at any time. Our company declines all responsibility of materials that do not comply with the rules prescribed in this document as well with the standards, the technical documents and the applicable professional standards. Any orders placed will be subject to our General Terms and Conditions of Sale, available on request. The drawings and/or images are the exclusive property of Pam Building and are confidential. They must not be reproduced or disclosed to any third party without written consent. They may only be used for the purpose for which they were issued and are returnable on request.