

ENSIGN SOIL Long Tail Corner Branch 88° EF036

DESCRIPTION

The long tail double corner branch is designed to offer a double branch off connection to a stack whether it be soil, vent or rainwater use. The long tail also allows for a jointless connection if being used to penetrate through a slab.

This product is designed and conforms to the design guidance of BS EN 12056-2.

RECOMMENDED USE

- Domestic use
- Wastewater
- Rainwater
- Runoff water
- Hot effluents

STANDARDS & APPROVALS

- Industry product standard: BS EN 877
- Range fire classification: A1

IDENTIFICATION LABEL





MATERIALS & COATINGS

- Cast Iron
- Internally and externally coated redbrown, anti-corrosive epoxy powder coating, average thickness 150 μm internally and 70μm externally

TECHNICAL FEATURES

- Hot water resistance: 24hr @ 95°C
- Thermal cycle resistance: 1500 cycles between 15°C and 93°C
- Chemical resistance for 2>ph>12
- Salt spray resistance internal coating: more than 350hrs.

ENVIRONMENTAL DATA


- Percentage of recycled content: 99%
- Recycling information: Cast Iron is 100% recyclable through the existing recycling industrial network.


Data source: Environmental Product Declaration S-P-02190



Long Tail Corner Branch 88° EF036







DN	L	н	w	A	В	С	D	E	F	WEIGHT (KG)	PRODUCT CODE
100x100	177	430	177	105	325	115	379	244	269	7.5	191559

This document is provided for information purposes, and our company reserves the right to modify the information contained herein at any time. Our company declines all responsibility of materials that do not comply with the rules prescribed in this document as well with the standards, the technical documents and the applicable professional standards. Any orders placed will be subject to our General Terms and Conditions of Sale, available on request. The drawings and/or images are the exclusive property of Pam Building and are confidential. They must not be reproduced or disclosed to any third party without written consent. They may only be used for the purpose for which they were issued and are returnable on request.