

ENSIGN SOIL

Split Band Mild-steel Bracket EF048SMBS

DESCRIPTION

The EF048SMBS Split band bracket is designed to strap around the pipe and offer a double anchor support.

This is then hung from both side of the bracket lugs using threaded rod which is hung from the construction slab to the builder's detail. For large diameters we recommend the use of 3 brackets per 3m length.

RECOMMENDED USE

- Domestic use
- Wastewater
- Rainwater
- Runoff water
- Hot effluents

STANDARDS & APPROVALS

- Industry product standard: BS EN 877
- Range fire classification: A1

IDENTIFICATION LABEL





MATERIALS & COATINGS

- Mild steel
- Internally and externally coated red-brown, anti-corrosive epoxy powder coating, average thickness 150 μm internally and $70 \mu m$ externally

TECHNICAL FEATURES

- Hot water resistance: 24hr @ 95°C
- Thermal cycle resistance: 1500 cycles between 15°C and 93°C
- Chemical resistance for 2>ph>12
- Salt spray resistance internal coating: more than 350hrs.

ENVIRONMENTAL DATA

- Percentage of recycled content: 99%
- Recycling information: Mild steel is 100% recyclable through the existing recycling industrial network.

Data source: Environmental Product Declaration S-P-02190





ENSIGN SOIL

Split Band

Mild-steel Bracket

EF048SMBS





DN	L	н	W	A	В	THREAD SIZE	WEIGHT (KG)	PRODUCT CODE
200	300	221	40	260	110.5	M12	0.99	285737
250	370	285.5	40	330	142.75	M12	1.26	285738
300	420	339.5	40	380	169.75	M12	1.82	285739
400	520	440	40	480	212	M14	2.30	261761
500	640	546	60	480	273	M16	6.81	261762

 Temporary bolt & nut fixings may be applied. Threaded bar for installation not included; please see above table regarding threaded bar requirements, dependant on diameter.

This document is provided for information purposes, and our company reserves the right to modify the information contained herein at any time. Our company declines all responsibility of materials that do not comply with the rules prescribed in this document as well with the standards, the technical documents and the applicable professional standards. Any orders placed will be subject to our General Terms and Conditions of Sale, available on request. The drawings and/or images are the exclusive property of Pam Building and are confidential. They must not be reproduced or disclosed to any third party without written consent. They may only be used for the purpose for which they were issued and are returnable on request.