

ENSIGN SOIL

Stack Support Bracket

EF051

DESCRIPTION

The stack support bracket is used in conjunction with the stack support pipe EF050 to offer extra support to the system.

When stack support pipes/brackets are required, use on any building with an average of 2.5m between floors, positioning stack support pipe at the base of the first floor, and every subsequent fifth floor thereafter. These are required for high rise buildings.

RECOMMENDED USE

- · Domestic use
- Wastewater
- Rainwater
- Runoff water
- · Hot effluents

STANDARDS & APPROVALS

- Industry product standard: BS EN 877
- Range fire classification: A1

IDENTIFICATION LABEL





MATERIALS & COATINGS

- Cast Iron
- Internally and externally coated red-brown, anti-corrosive epoxy powder coating, average thickness 150 µm internally and 70µm externally
- EPDM rubber gasket

TECHNICAL FEATURES

- Hot water resistance: 24hr @ 95°C
- Thermal cycle resistance: 1500 cycles between 15°C and 93°C
- Chemical resistance for 2>ph>12
- Salt spray resistance internal coating: more than 350hrs.

ENVIRONMENTAL DATA


- Percentage of recycled content: 99%
- Recycling information: Cast Iron is 100% recyclable through the existing recycling industrial network.

Data source: Environmental Product Declaration S-P-02190



Stack Support Bracket EF051





DN	L	н	w	A	В	С	WEIGHT (KG)	PRODUCT CODE
70	215	20	150	170	30	128	1.1	191857
100	259	20	184	214	32	162	1.5	191843
125	275	20	209.5	228	32	187	1.7	191844
150	300	22	240	255	32	224	2.6	191845
200	362	22	293	310	36	278	3.5	*157014
250	444	40	363	394	40	354	6.1	*157097
300	498	40	415	448	40	406.5	14.0	*157160

^{*}Complete with stack support pipe EF050

This document is provided for information purposes, and our company reserves the right to modify the information contained herein at any time. Our company declines all responsibility of materials that do not comply with the rules prescribed in this document as well with the standards, the technical documents and the applicable professional standards. Any orders placed will be subject to our General Terms and Conditions of Sale, available on request. The drawings and/or images are the exclusive property of Pam Building and are confidential. They must not be reproduced or disclosed to any third party without written consent. They may only be used for the purpose for which they were issued and are returnable on request.