

ENSIGN SOIL

Double 90° Boss Pipe EF092

DESCRIPTION

The double 90° boss pipe offers two 90° 50mm bosses for connecting a SVP stack to waste connections, mainly mid/low level waste. The 50mm boss is designed to connect 50-54mm uPVC/HDPE/Copper waste connections.

This product is designed and conforms to the design guidance of BS EN 12056-2.

RECOMMENDED USE

- Domestic use
- Wastewater
- Rainwater
- Runoff water
- Hot effluents

STANDARDS & APPROVALS

- Industry product standard: BS EN 877
- Range fire classification: A1

IDENTIFICATION LABEL





MATERIALS & COATINGS

- Cast Iron
- Internally and externally coated red-brown, anticorrosive epoxy powder coating, average thickness 150 µm internally and 70µm externally
- Gasket: EPDM rubber EN 681
- Zinc & Clear Mild Steel Hex Head Bolts (M8) with matching Nut

TECHNICAL FEATURES

- Hot water resistance: 24hr @ 95°C
- Thermal cycle resistance: 1500 cycles between 15°C and 93°C
- Chemical resistance for 2>ph>12
- Salt spray resistance internal coating: more than 350hrs.


ENVIRONMENTAL DATA

- Percentage of recycled content: 99%
- Recycling information: Cast Iron is 100% recyclable through the existing recycling industrial network.


Data source: Environmental Product Declaration S-P-02190



Double 90° Boss Pipe EF092







DN	L	н	W	WEIGHT (KG)	PRODUCT CODE
100	150	155	150	2.9	191849





- Plastic moulded protection caps (10 pack) EF093, are available for temporarily blanking off boss connections. Product code: 192255
- O-Ring Gasket spares-kit (10 pack). Product code: 259491